



Daikin Altherma 3

ERLA

- Sound pressure level as low as 48 dBA for minimal noise disruption
- Utilises the eco-friendly R-32 refrigerant with a low GWP, ensuring sustainable operation
- Slim dimensions for easy installation in various spaces
- Lower energy consumption thanks to its high energy efficiency
- W-LAN adapter and cartridge connection (optional)
- Black grille hiding the fan from view

Altherma 3 ERLA

Specification	Model	
Specification	ERLA16D2W17	ERLA16DAW17
Sound Pressure Level (Heating)	48.0 (2) dBA	48.0 (2) dBA
Sound Power Level (Heating)	62.0 (2) dBA	62.0 (2) dBA
Refrigerant		
GWP	675.0	675.0
Charge (kg)	3.80	3.80
Type	R-32	R-32
Dimensions (mm)		
Width	1,100	1,100
Depth	460	460
Height	870	870
Weight (kg)	101	101
Operation Range (Cooling)		
Max. °CDB	43	43
Min. °CDB	10	10
Domestic Hot Water		
Ambient Min. °CDB	-25	-25
Ambient Max. °CDB	25 (1), 35 (1)	25 (1), 35 (1)
Fan Air Flow Rate (High, m³/min)		
Heating	85.0	85.0
Cooling	85.0	85.0
Piping Connections		
Heat Insulation	Both liquid and gas pipes	Both liquid and gas pipes
Liquid OD (mm)	9.50	9.50
Gas OD (mm)	15.9	15.9
Drain OD (mm)	26	26
Level Difference IU-OU (Max. m)	30.0	30.0
Power Supply		
Phase	3~	3~
Name	W1	W1
Frequency (Hz)	50	50
Voltage (V)	400	400
Current (A)	16	16